

Verosol® SilverScreen

Metallised 4% openness Verosol® SilverScreen 205 Performance









Features

SilverScreen 205 Performance metal backed screen provides excellent vision out, and dramatically reduces heat and glare at the window, independent of colour. The fabric offers an unparalleled solar reflectance of 77%. Constructed from a hard wearing PVC coated fibreglass, SilverScreen is inherently flame retardant.

Care Instructions

Verosol fabrics are anti-static and therefore dust repellent. For regular maintenance, use a soft feather duster or vacuum-clean with a soft brush in a low setting.

Colour Options

							
0050 Black	0040 Dark Grey	0070 Chocolate Brown	0060 Bronze	0100 Dark Beige	0020 Beige	0030 Light Grey	0010 White



green building council australia
MEMBER 2015-2016



Fire retardant
AS1530 part 2

Weathermaster®

Verosol® SilverScreen 205 Performance

Technical information









Fabric Density	Semi Transparent
Composition	64% PVC / 36% Fibreglass
Weight	400gsm ± 5%
Thickness	0.5mm ± 5%
Width	2400mm
Colour Fastness	7 - 8 [ISO 105-B02]
Flame Retardancy	Independently tested to AS1530 part 2. Flammability Index: 1 Range [0-20]
Organic emissions (VOC)	Greenguard Gold certified, Oeko-Tex 100 Class IV. Does not exceed the maximum Volatile Organic Compound criteria specified by the Green Building Council of Australia (IEQ-11).
Product Options	Roller Blinds

Fabric colour code	0050	0040	0070	0060	0100	0020	0030	0010
--------------------	------	------	------	------	------	------	------	------

Optical/Light properties								
Visual Light Transmittance	5%	4%	5%	5%	5%	6%	5%	6%
Openness factor (nominal)	4%	4%	4%	4%	4%	4%	4%	4%
Heat/Solar properties								
Solar transmittance	4%	4%	4%	4%	5%	6%	5%	6%
Solar reflectance outside	76%	76%	78%	78%	78%	77%	77%	77%
Solar absorptance	20%	20%	18%	18%	17%	17%	18%	17%
G-value / Solar heat gain coefficient								
Glazing Type - Single 4mm Clear Glass	20%	18%	18%	19%	18%	19%	19%	19%

For more information please contact New Zealand Window Shades on 0800 223 224 or <https://www.weathermaster.co.nz/>

Colour Options

							
0050 Black	0040 Dark Grey	0070 Chocolate Brown	0060 Bronze	0100 Dark Beige	0020 Beige	0030 Light Grey	0010 White

New Zealand Window Shades Ltd.

PO Box 12 785, Penrose, Auckland 1642, New Zealand

Weathermaster® is a division of New Zealand Window Shades Ltd.

©Copyright 2021 New Zealand Window Shades Ltd.



Fire retardant
AS1530 part 2

Weathermaster®